



Atlanta Athletic Club

PUMP STATIONS AND FILTRATION

System-Powering Performance and Efficiency.

Rain Bird applies our world-leading irrigation expertise to the design and manufacture of golf pump stations and filters. As part of a fully integrated Rain Bird irrigation system, these pump stations bring real-time response to your pump, monitoring the operation of the pump and maximizing flow throughout the irrigation cycle. You'll get reduced water use, lower energy costs and less wear and tear on your pump station.



Designed for Durability

Rain Bird® pump stations and filters are built to the highest quality standards. Whether it's a sophisticated suppression system that reduces the risk of electronic component damage or a durable polyester powder coating that protects the appearance of your investment, these pumps and filters offer enduring performance.

A Fit for Any Environment or Budget

Every Rain Bird pump station is custom built for the specific requirements of your course, offering a variety of options that make it easier to achieve the most efficient performance possible.





HORIZONTAL PUMPS						
	Pump Direction and Number	Motor (with VFD)	Max psi (bar)	Max gpm (lps) (m ³ /h)	Enclosure	Display
HES1	One horizontal end suction pump	15 to 60 HP	125 psi (8.6 bar)	600 gpm (37.8 lps, 136.3 m ³ /h)	Aluminum	Monochrome touch-panel Optional color touch-panel
HES2	Two horizontal end suction pumps	15 to 60 HP	125 psi (8.6 bar)	1200 gpm (76 lps, 273 m ³ /h)	Aluminum	Monochrome touch-panel Optional color touch-panel
HES3	Three horizontal end suction pumps	20 to 60 HP	125 psi (8.6 bar)	1800 gpm (114 lps, 409 m ³ /h)	Aluminum	Monochrome touch-panel Optional color touch-panel




VERTICAL PUMPS						
	Pump Direction and Number	Motor (with VFD)	Max psi (bar)	Max gpm (lps) (m ³ /h)	Enclosure	Display
VM1	One vertical multistage pump	15 to 60 HP	155 psi (10.7 bar)	500 gpm (31.5 lps, 113.6 m ³ /h)	Aluminum	Monochrome touch-panel Optional color touch-panel
VM2	Two vertical multistage pumps	15 to 60 HP	150 psi (10.3 bar)	1000 gpm (63.1 lps, 227 m ³ /h)	Aluminum	Monochrome touch-panel Optional color touch-panel



PANEL ONLY			
	Number of Pumps	Motor Type	Additional Accessories
Panel	Controls 1 to 10 pumps up to 100 HP each	VFD or VPM	Flow meter and pressure transducer included



COMPACT DECKS		
Features	VT1	VT2
Motor (with VFD)	15 to 75 HP	25 to 75 HP
Max psi (bar)	140 psi (9.7 bar)	140 psi (9.7 bar)
Max gpm (lps) (m ³ /h)	800 gpm (51 lps, 181 m ³ /h)	1600 gpm (101 lps, 363 m ³ /h)
Display	Color touch-panel	Color touch-panel



LARGE DECKS			
Features	VT2	VT3	VT4
Integrated Filtration	Yes	Yes	Yes
Motor (with VFD)	20 to 100 HP	40 to 100 HP	40 to 100 HP
Max psi (bar)	140 psi (9.7 bar)	140 psi (9.7 bar)	140 psi (9.7 bar)
Max gpm (lps) (m ³ /h)	2000 gpm (126 lps, 454 m ³ /h)	3000 gpm (189 lps, 681 m ³ /h)	4000 gpm (252 lps, 908 m ³ /h)
Display	Color touch-panel	Color touch-panel	Color touch-panel

VT-Custom

- Custom-designed to meet your requirements.
- Provide us with your specifications.

Remote Pump Station Access

Rain Bird's user interface is a network ready design that allows for remote access via PC, laptop, tablet, smart phone or any web-enabled mobile device. The screen always formats properly to the remote device and allows complete control and monitoring of the golf pump station. This remote accessibility provides Rain Bird customers the confidence to control their pumping systems when they are away from the course.

Electrical Design

Rain Bird® pump stations are UL508A listed and use the industry's best surge suppression, reducing the risk of electronic component damage that could lead to inconvenient and costly downtime. This design includes full heavy-duty circuit breaker integration providing the ultimate protection with the best serviceability.

Backup Pressure Regulation

Every station comes with a properly sized pressure relief valve to provide automatic pressure regulation in the event of an overpressure situation.

VFD Per Motor (VPM) Option

Rain Bird offers the industry's most comprehensive catalog of customer-focused solutions, including a VFD for each main motor on a multi-pump station. This option provides superior flow and pressure regulation, and eliminates mechanical switching components, increasing uptime. It also provides a level of efficient backup pressure regulation that a pressure relief valve or butterfly valve cannot deliver.

Durable Polyester Powder-Coating

Rain Bird's in-house steel-grit blasting system assures all exterior surfaces of the pump station are prepared to white metal specification standards and allows for the best coating adhesion. The polyester powder-coat Rain Bird applies is far more durable than competitive solvent-based multi-layer coatings. In fact, Rain Bird's powder-coating process scores a 10 out of 10 on an ASTM corrosion test provided by Sherwin Williams. Other industry pump stations scored four (4) out of 10 on the very same test. In addition the powder-coating process is considered very environmentally friendly.

Engineered Pump Station Skid Design

Using 3D modeling, the channel steel skid frame is engineered for strength and rigidity. This engineered design reduces vibration and eliminates the need for raised, extra-thick steel plates under the pump heads, which can be a trip hazard. The deck is the industry's strongest and longest lasting with continuously welded smooth steel plate. In addition, Rain Bird follows industry standards and manufacturers' recommendations for station components such as the proper specifications for flow meters.

Advanced Controls

With the industry's leading touch screens, Rain Bird continues to innovate by offering sizes up to 15". Beyond being network ready, this interface offers up to 20 years of historical memory capability and USB backup. With features such as filtration integration, water feature control, lake level control, pump lockouts, auto set point adjustment per pump, motor starts protection, and many more, Rain Bird has driven pump station innovation in the golf industry for the last decade.

Real-Time System Integration

Rain Bird pump stations have Pump Manager 2 and Smart Pump™ technology at the central control, so you can configure your system to automatically monitor and self-adjust to changing conditions. This seamless integration by Rain Bird improves your system's overall performance by reducing watering windows and minimizing energy use.

Pump and Motor Options

Rain Bird offers custom designed cast ductile iron discharge heads for golf irrigation pump stations. With superior flow characteristics and 12 times the required tensile strength for golf pump stations, they are the obvious choice for the application. Rain Bird utilizes G.E. motors with industry-leading warranties, efficiencies and durability.

Air Relief

Rain Bird provides air relief on each pump. Individual air relief valves allow for the maximum amount of air to be removed from the pump columns and not enter into the irrigation system.

User Controls

Rain Bird pump stations have set the bar with simple, large-icon touchscreen controls in nine (9) different languages. Each pump has a lighted, three position Manual-Off-Auto switch for intuitive, safe backup control of the station.

PUMP STATIONS AND FILTRATION



Custom colors available.

Pump Manager 2

Rain Bird® Pump Manager 2 is engineered for the golf course professional looking to simplify pump control, monitoring and data reporting. This powerful software application gives you full control of your pump station from your computer or central control.

FEATURES AND BENEFITS

- Provides a direct link to the pump station touchscreen so you can view and modify pump operations from your computer or tablet as though you were standing right in front of it.
- Since all pump operation data is contained on your computer, Pump Manager 2 and its built-in reporting capabilities can keep you apprised of operations, flow, water use and other key information.
- Includes common reports for future review or regulatory reporting.
- For customized reporting, data can be exported in a file compatible with common spreadsheet applications such as Microsoft® Excel®.
- Standard with 11 different language options.
- Can be used with any computer and provide remote monitoring for any irrigation system using a competitive control system.
- Best of all, Pump Manager 2 is fully integrated with Rain Bird's exclusive central control feature, Smart Pump™.



Smart Pump™

FEATURES AND BENEFITS

Rain Bird's Smart Pump is a powerful central control software tool that improves pump station performance more than any comparable product on the market. It integrates your irrigation system from reservoir to rotor, constantly comparing actual flow to expected flow. By making smart, real-time decisions based on this information, it optimizes your system — saving water, conserving electricity and reducing wear and tear on your valuable pumping system.

Actual Flow Measurement

Unlike other irrigation central control software, Smart Pump bases its decisions on actual flow, not estimated flow. By using accurate information — in real time — Smart Pump automatically balances supply with system demand. That means greater efficiency and an end to wasted water and electricity.

24-Hour Pump Supervision

With Smart Pump, you can relax knowing your system will instantly respond to actual field conditions with the right decisions. For instance, if a pipe breaks, Smart Pump will stop water flow to the pipe to prevent turf damage. Or if a pump fails, Smart Pump will make immediate water demand adjustments to keep the system from shutting down permanently. It's like having your own irrigation supervisor at every sprinkler, 24/7.

Integration Meets Intelligence

Smart Pump seamlessly integrates your entire irrigation system. It automatically starts waiting sprinklers or pauses active sprinklers to reduce flow or increase demand, keeping your irrigation system running at peak efficiency at all times.

HOW TO SPECIFY

SMARTPUMPM

MODEL
Smart Pump

Self-cleaning line powered hydraulic water filters for turf, landscape, agriculture, greenhouse, golf course and nursery applications.

FEATURES

- **Flow Rate:** 15 – 7,350 gpm
- **Max Temperature:** 210° F
- **Flushing Operations:** Single electric ball valve for flushing operations standard
- **Screen:** 316 L stainless steel sintered screens standard
- **Screen Opening:** 5 μ – 4000 μ
- **Working Pressure:** 35 – 150 psi
- **Material:** Stainless Steel, Powder Coated Carbon Steel, Duplex Steel¹ or Fiberglass Reinforced Plastic
- **Configurations Available:** Filter only, or a complete assembly with bypass manifold and valves



Performance Data

Model Number		Line Size (in)	Standard Flow Rate (gpm)				Sintered Screen Area		Flush Volume (gal)	Flush Line Size (in)	Min. Inlet Pressure During Rinse Cycle (psi)
Powder-Coated Carbon Steel	Stainless Steel		MICRON MESH	300 50	200 80	120 125	100 140	(ft ²)			
HS-I-02-A	HS-I-02-A-S	2	200	200	200	200	2.65	382	15 to 50	1.5	35
HS-I-03-A	HS-I-03-A-S	3	300	300	300	300	2.65	382	15 to 50	1.5	35
HS-I-04-A	HS-I-04-A-S	4	500	500	500	500	2.65	382	15 to 50	1.5	35
HS-I-04-B	HS-I-04-B-S	4	500	500	500	500	5.25	756	15 to 50	1.5	35
HS-I-04-C	HS-I-04-C-S	4	500	500	500	500	7.00	1008	15 to 50	1.5	35
HS-I-04-D	HS-I-04-D-S	4	500	500	500	500	9.25	1332	35 to 110	2.0	35
HS-I-06-A	HS-I-06-A-S	6	650	630	555	530	2.65	382	15 to 50	1.5	35
HS-I-06-B	HS-I-06-B-S	6	1000	1000	1000	1000	5.25	756	15 to 50	1.5	35
HS-I-06-C	HS-I-06-C-S	6	1000	1000	1000	1000	7.00	1008	15 to 50	1.5	35
HS-I-06-D	HS-I-06-D-S	6	1000	1000	1000	1000	9.25	1332	35 to 110	2.0	35
HS-I-08-B	HS-I-08-B-S	8	1400	1260	1100	1050	5.25	756	15 to 50	1.5	35
HS-I-08-C	HS-I-08-C-S	8	1700	1680	1470	1400	7.00	1008	15 to 50	1.5	35
HS-I-08-D	HS-I-08-D-S	8	2000	2000	1943	1850	9.25	1332	35 to 110	2.0	35
HS-I-10-C	HS-I-10-C-S	10	1900	1680	1470	1400	7.00	1008	15 to 50	1.5	35
HS-I-10-D	HS-I-10-D-S	10	2000	2000	1943	1850	9.25	1332	35 to 110	2.0	35
HS-I-10-E	HS-I-10-E-S	10	2700	2700	2573	2450	12.25	1764	35 to 110	2.0	35
HS-I-12-D	HS-I-12-D-S	12	2000	2000	1943	1850	9.25	1332	35 to 110	2.0	35
HS-I-12-E	HS-I-12-E-S	12	3100	2940	2573	2450	12.25	1764	35 to 110	2.0	35
HS-I-12-F	HS-I-12-F-S	12	3800	3660	3200	3050	15.25	2196	35 to 110	2.0	35
HS-I-14-E	HS-I-14-E-S	14	3100	2940	2573	2450	12.25	1764	35 to 110	2.0	35
HS-I-14-F	HS-I-14-F-S	14	3800	3660	3200	3050	15.25	2196	35 to 110	2.0	35
HS-I-14-G	HS-I-14-G-S	14	4500	4320	3780	3600	18.00	2592	35 to 110	2.0	35
HS-I-16-E	HS-I-16-E-S	16	3100	2940	2573	2450	12.25	1764	35 to 110	2.0	35
HS-I-16-F	HS-I-16-F-S	16	3800	3660	3200	3050	15.25	2196	35 to 110	2.0	35
HS-I-16-G	HS-I-16-G-S	16	4500	4320	3780	3600	18.00	2592	35 to 110	2.0	35
HS-I-16-H	HS-I-16-H-S	16	6125	5880	5145	4900	24.50	3528	35 to 110	2.0	35
HS-I-18-F	HS-I-18-F-S	18	3800	3660	3200	3050	15.25	2196	35 to 110	2.0	35
HS-I-18-G	HS-I-18-G-S	18	4500	4320	3780	3600	18.00	2592	35 to 110	2.0	35
HS-I-18-H	HS-I-18-H-S	18	6125	5880	5145	4900	24.50	3528	35 to 110	2.0	35
HS-I-20-G	HS-I-20-G-S	20	4500	4320	3780	3600	18.00	2592	35 to 110	2.0	35
HS-I-20-H	HS-I-20-H-S	20	7350	5880	5145	4900	24.50	3528	35 to 110	2.0	35
HS-I-24-H	HS-I-24-H-S	24	7350	5880	5145	4900	24.50	3528	35 to 110	2.0	35
HS-I-30-H	HS-I-30-H-S	30	7350	5880	5145	4900	24.50	3528	35 to 110	2.0	35

All models have a rinse duration of 10 to 30 seconds.