


- ① FINISH GRADE/TOP OF MULCH
- ② ROOT WATERING SERIES:
RAIN BIRD RWS-S SERIES
(TYPICAL)
- ③ 1/2-INCH SPIRAL BARB FITTING
(INCLUDED) (TYPICAL)
- ④ 1/2-INCH SWING ASSEMBLY:
RAIN BIRD SA-125050
OR
1/2-INCH SWING PIPE:
RAIN BIRD SP SERIES WITH
1/2-INCH MALE NPT x
.490-INCH BARB ELBOW:
RAIN BIRD SBE-050
(TYPICAL)
- ⑤ PVC SCH 40 TEE OR EL (TYPICAL)
- ⑥ PVC OR POLYETHYLENE LATERAL
PIPE
- ⑦ SHRUB ROOT BALL

NOTES:

- 1. PLACE TOP OF RWS-S EVEN WITH FINISH GRADE OR TOP OF MULCH.
- 2. SPACE RWS-S EVENLY BETWEEN SHRUBS, AS SHOWN ABOVE.
- 3. RWS-S IS AVAILABLE IN THE FOLLOWING MODELS:
RWS-S-B-C-1401 (0.5 GPM, CHECK VALVE)
RWS-S-B-1401 (0.5 GPM)
- 4. ONCE RWS-S HAS BEEN INSTALLED FILL THE BASKET WITH PEA GRAVEL BEFORE REPLACING SNAP-ON LID.



ROOT WATERING SYSTEM
N.T.S. **RWS-S Shrub Installation**

3-3-10