



Certification of Performance

The products below have been tested to meet the requirements of the ASABE/ICC 802-2014 standard.

The average DU(LQ) of the applicable products exceed 0.65 distribution uniformity.

High-Efficiency Sprinklers			
Products	Type	Radius	DU(LQ)
HE-VAN	Spray, Variable Arc	6 - 15 ft.	> 0.70
U-Series	Spray, Fixed Arc	6 - 15 ft.	> 0.70
R-VAN	Multi-stream, Variable Arc	8 - 24 ft.	> 0.70
R-Series	Multi-stream, Fixed Arc	13 - 24 ft.	> 0.70
3500 Series	Rotors	15 - 35 ft.	> 0.75
5000 Series*	Rotors	25 - 50 ft.	> 0.70
6504 Series	Rotors	39 - 65 ft.	> 0.80
8005 Series	Rotors	39 - 81 ft.	> 0.75
RD1800 Series	P30 and P45 Pressure Regulated Spray Bodies		
1800 Series	P30 and P45 Pressure Regulated Spray Bodies		

Drips, Emitters and Bubblers
Products
All 5-Series, 1300A-F and 1400-Series Bubblers
All Dripline/Inline Emitter Tubing
All Point Source Emitters
Root Watering Systems
SQ Series Square Pattern Nozzles
Xeri-Series Sprays and Misters

* Applies to all *standard angle* Rain Curtain Nozzles except the 8.0 gpm nozzle.

Rain Bird Corporation and its subsidiaries (Rain Bird) reserve the right to make corrections, enhancements, improvements and other changes to its products and reported test results.