



**T-Bird**



**T-Bird with T-22 & T-40 Turret Performance**

Pressure psi	Nozzle	Radius ft.	Flow GPM	■	▲
				Precip In/h	Precip In/h
25	T22-1.3	21	1.20	0.52	0.61
	T40-1.0	26	0.90	0.26	0.30
	T40-1.5	28	1.60	0.39	0.45
	T40-2.0	32	1.90	0.36	0.41
	T40-3.0	34	2.80	0.47	0.54
35	T22-1.3	22	1.30	0.52	0.60
	T40-1.0	26	1.10	0.31	0.36
	T40-1.5	30	1.90	0.41	0.47
	T40-2.0	33	2.20	0.39	0.45
	T40-3.0	35	3.30	0.52	0.60
45	T22-1.3	22	1.32	0.53	0.61
	T40-1.0	27	1.20	0.32	0.37
	T40-1.5	31	2.20	0.44	0.51
	T40-2.0	34	2.60	0.43	0.50
	T40-3.0	36	3.80	0.56	0.65
55	T22-1.3	22	1.35	0.54	0.62
	T40-1.0	27	1.40	0.37	0.43
	T40-1.5	31	2.40	0.48	0.56
	T40-2.0	34	2.90	0.48	0.56
	T40-3.0	36	4.10	0.61	0.70
65	T40-1.0	26	1.50	0.43	0.49
	T40-1.5	31	2.70	0.54	0.62
	T40-2.0	34	3.10	0.52	0.60
	T40-3.0	36	4.50	0.67	0.77

**AG-5 / AG-5 SAM Maxi-Paw Performance**

Pressure psi	Nozzle	Radius ft.	Flow GPM	■	▲
				Precip In/h	Precip In/h
25	06	-	-	-	-
	07	36	1.9	0.41	0.48
	08	37	2.8	0.44	0.51
	10	40	4.2	0.56	0.65
	12	39	5.5	0.70	0.80
35	06	36	1.6	0.28	0.32
	07	38	2.3	0.38	0.44
	08	38	3.3	0.44	0.51
	10	41	4.8	0.55	0.64
	12	42	6.3	0.69	0.79
40	06	38	1.8	0.30	0.33
	07	39	2.4	0.38	0.44
	08	39	3.5	0.45	0.51
	10	41	5.2	0.58	0.67
	12	44	6.7	0.70	0.80
45	06	38	1.9	0.31	0.35
	07	39	2.5	0.38	0.44
	08	40	3.7	0.45	0.51
	10	42	5.4	0.59	0.68
	12	44	7.1	0.71	0.82
50	06	38	2.0	0.31	0.37
	07	40	2.7	0.38	0.44
	08	41	3.9	0.45	0.52
	10	44	5.7	0.61	0.73
	12	45	7.4	0.73	0.85
55	06	38	2.1	0.33	0.39
	07	41	2.8	0.38	0.44
	08	41	4.1	0.47	0.54
	10	44	6.0	0.62	0.72
	12	45	7.9	0.75	0.87
60	06	38	2.2	0.35	0.40
	07	41	2.9	0.40	0.46
	08	42	4.2	0.46	0.53
	10	44	6.4	0.64	0.74
	12	45	8.4	0.80	0.92

Unique Quality Features