

Rain Bird 45 psi 1800 Series Spray Head

How To Specify

1804 - SAM - PRS - P45

Optional Feature SAM
Seal-A-Matic™ check valve

Optional Feature PRS: 30psi (2.1 bar) in-stem pressure regulation

P45: 45psi (3.1 bar) in-stem pressure regulation

Model

1804: 4" (10.2 cm) pop-up height

Note: SAM feature included with P45 models

How To Specify

1804 - SAM-P45 - R13-18Q

Optional Feature SAM
Seal-A-Matic™ check valve
P45: 45psi (3.1 bar) in-stem pressure regulation

Nozzle
Rotary Nozzle

Radius Range
13-18' (4.0 – 5.5,m)
17-24' (5.2 – 7.3m)

Pattern
F: Full (360°)
TQ: Three Quarter (270°)
TT: Two Third (240°)
H: Half (180°)
T: Third (120°)
Q: Quarter (90°)

Model

1804: 4" (10.2 cm) pop-up height

Note: Specify sprinkler bodies and nozzles separately.

Improve Performance, Save Water.

Overview

- Delivers the unbeatable combination of over 30 years of trusted 1800 Series Spray Head performance and the highly efficient and low precipitation rate of the Rotary Nozzle
- Saves water. Using Rotary Nozzles with 45 psi 1800 Series Spray Heads can cut water use by up to 65%

Features

- Provides 45 psi in-stem pressure regulation for maximizing efficiency of Rotary Nozzles
- Includes Seal-A-Matic (SAM) check valve preventing low head drainage of up to 14 feet of head
- Available in 4", 6", and 12" models



Easy to read identification markings on the 45 psi 1800 Series Spray Head and Rotary Nozzle simplify inventory, installation and inspection.

For more information on the 45 psi 1800 Series Spray Head and to view an interactive Flash demo visit www.rainbird.com/landscape/products/sprays

