



- ① RAIN BIRD ET MANAGER TIPPING RAIN GAUGE:  
RAIN BIRD ETM-RG (DIMENSIONS  $3\frac{5}{16}$ " H X  
 $1\frac{5}{16}$ " W X  $3\frac{7}{8}$ " D)
- ② RAIN BIRD ET MANAGER
- ③ SOLID BARE COPPER WIRE (#10 AWG MIN.)  
FROM ET MANAGER TO GROUNDING GRID.  
MAKE WIRE AS SHORT AND STRAIGHT AS  
POSSIBLE.
- ④ RAIN TIP TERMINAL FOR CONNECTION TO  
TIPPING RAIN GAUGE
- ⑤ 30' LENGTH OF WIRE TO TIPPING RAIN GAUGE  
(INCLUDED). CUT TO REQUIRED LENGTH. IF  
ADDITIONAL DISTANCE IS REQUIRED THE RAIN  
GAUGE CAN HAVE A MAXIMUM CABLE RUN  
OF 500'. USE 18 AWG AS A MINIMUM WIRE  
SIZE FOR ADDITIONAL CABLE.
- ⑥ MOUNTING SCREWS (NOT INCLUDED)
- ⑦ MOUNTING PLATE WITH 2 MOUNTING HOLES
- ⑧ WIRE NOTCH
- ⑨ RAIN DRAINAGE HOLES
- ⑩ LEVEL SURFACE OR BRACKET

D

## Tipping Rain Gauge with ET Manager

N.T.S.

2-04-09