

Twist Lock Fittings


TLF Series

Rain Bird's complete line of Twist Lock Fittings simplify the installation of all industry standard 1/2", 3/4" and 1" dripline and distribution tubing. They provide an even tighter seal on tubing by using high quality barbs and twist-locking nuts. Their unique barb design reduces insertion force while maintaining a secure fit.

Ideal for use with Rain Bird XFD, XFS and XFCV dripline, XF blank tubing, XT700, XBS and QF Header distribution tubing. Models include couplings, elbows, tees, caps and MPT threaded adapters.

FEATURES

- Complete line of Twist Lock Fittings to simplify installation of Dripline and blank distribution tubing
- Fittings provide an even tighter seal on tubing by using high quality barbs and twist locking nuts
- Unique barb design reduces insertion force while maintaining a secure fit



MODELS



600 Series (1/2")

- **TLF-CUPL-0600**
Twist Lock Coupling
1/2" x 1/2"
- **TLF-TEE-0600**
Twist Lock Tee
1/2" x 1/2" x 1/2"
- **TLF-ELBW-0600**
Twist Lock Elbow
1/2" x 1/2"
- **TLF-MPT6-0600**
Twist Lock MPT Thread
Male Adaptor
1/2" x 1/2" MPT
- **TLF-MPT8-0600**
Twist Lock MPT Thread
Male Adaptor
1/2" x 1/2" MPT



800 Series (3/4")

- **TLF-CUPL-0800**
Twist Lock Coupling
3/4" x 3/4"
- **TLF-TEE-0800**
Twist Lock Tee
3/4" x 3/4" x 3/4"
- **TLF-ELBW-0800**
Twist Lock Elbow
3/4" x 3/4"
- **TLF-MPT8-0800**
Twist Lock MPT Thread
Male Adaptor
3/4" x 3/4" MPT
- **TLF-CAP-0800**
Fitting Cap - Fits on
TLF-MPT8-0800 &
TLF-MPT8-0600




1000 Series (1")

- **TLF-CUPL-1000**
Twist Lock Coupling
1" x 1"
- **TLF-TEE-1000**
Twist Lock Tee
1" x 1" x 1"
- **TLF-ELBW-1000**
Twist Lock Elbow
1" x 1"
- **TLF-MPT1-1000**
Twist Lock MPT
Thread Male Adaptor
1" x 1" MPT

How To Specify

TLF - CUPL - 0600



Size:
0600 - 1/2" Tubing
0800 - 3/4" Tubing
1000 - 1" Tubing

Fitting Type:

CUPL = Coupling
TEE = Tee
ELBW - Elbow
MPT6 - 1/2" Male Pipe Threading
MPT8 - 3/4" Male Pipe Threading
MPT1 - 1" Male Pipe Threading

	600 Series		800 Series		1000 Series	
	Inches	mm	Inches	mm	Inches	mm
	Acceptable Internal Diameter	0.590 to 0.630	15.00 to 16.00	0.790 to 0.845	20.0 to 21.5	1.025 to 1.085
Acceptable Wall Thickness	0.025 to 0.050	0.64 to 1.27	0.045 to 0.065	1.14 to 1.65	0.045 to 0.065	1.14 to 1.65
Operating Range	0 - 60 PSI					

	Models	Tubing					
		XFD Dripline & Blank	XT700	1/2" XBS	3/4" XBS	3/4" QF Header	1" QF Header
600 Series: 1/2"	 TLF-CUPL-0600	✓	✓	✓			
	 TLF-TEE-0600	✓	✓	✓			
	 TLF-ELBW-0600	✓	✓	✓			
	 TLF-MPT6-0600	✓	✓	✓			
	 Uses TLF-CAP-800 TLF-MPT8-0600	✓	✓	✓			
800 Series: 3/4"	 TLF-CUPL-0800				✓	✓	
	 TLF-TEE-0800				✓	✓	
	 TLF-ELBW-0800				✓	✓	
	 Uses TLF-CAP-800 TLF-MPT8-0800				✓	✓	
	 TLF-CAP-0800				✓	✓	
1000 Series: 1"	 TLF-CUPL-1000						✓
	 TLF-TEE-1000						✓
	 TLF-ELBW-1000						✓
	 TLF-MPT1-1000						✓

Rain Bird Corporation
6991 E. Southpoint Road
Tucson, AZ 85756
Phone: (520) 741-6100
Fax: (520) 741-6522

Rain Bird Corporation
970 West Sierra Madre Avenue
Azusa, CA 91702
Phone: (626) 812-3400
Fax: (626) 812-3411

Rain Bird International, Inc.
1000 West Sierra Madre Ave.
Azusa, CA 91702
Phone: (626) 963-9311
Fax: (626) 852-7343

Rain Bird Technical Services
(800) RAINBIRD (1-800-724-6247)
(U.S. and Canada)

Specification Hotline
800-458-3005 (U.S. and Canada)

The Intelligent Use of Water™
www.rainbird.com