

- PRESSURE-COMPENSATING MODULE BARB INLET X BARB OUTLET EMITTER WITH PC DIFFUSER CAP: RAIN BIRD PC EMITTER WITH PC DIFFUSER
- 2) UNIVERSAL ¼" TUBING STAKE: RAIN BIRD TS-025
- 3)¼" DISTRIBUTION TUBING: RAIN BIRD XQ TUBING (LENGTH AS REQUIRED)
- 4) TOP OF MULCH
- 5)¼" SELF-PIERCING BARB CONNECTOR: RAIN BIRD SPB-025
- (6)½" POLYETHYLENE TUBING: RAIN BIRD XF SERIES TUBING OR RAIN BIRD XT-700 XERI-TUBE OR RAIN BIRD XBS BLACK STRIPE TUBING

1-13-10

) FINISH GRADE

NOTES:

- 1. USE RAIN BIRD XERIMAN TOOL XM-TOOL TO INSERT EMITTER
- DIRECTLY INTO ½" POLYETHYLENE TUBING.
 2. SHOULD THE EMITTER BECOME DISLODGED UNREGULATED FLOW WILL OCCUR.
- 3. RAIN BIRD PC BARB X BARB EMITTERS ARE AVAILABLE IN THE FOLLOWING MODELS:

PC-05 5 GPH PC-07 7 GPH PC-10 10 GPH PC-12 12 GPH PC-18 18 GPH PC-24 24 GPH

4. PC DIFFUSER CAPS ARE AVAILABLE IN BOTH BLACK AND PURPLE.



PRESSURE COMPENSATING MODULE WITH PC DIFFUSER CAP FROM BARB CONNECTOR

INTO 1/2" TUBING WITH 1/4' TUBING, STAKE AND BUG CAP - OPTION 3

N.T.S.