



80E

1 1/4" (32 mm) Full Circle, Brass Impact Sprinkler

Bearing: 1 1/4" Male NPT or BSP, Brass

Trajectory Angle: 27°

Operating Range: 1.7-6.9 bars

Flow Rate: 3.88-29.00 m³/h

Radius: 18.61-35.38 meters

FEATURES

- Heavy duty brass construction
- Internal plastic straightening vane
- Stainless steel springs and fulcrum pin
- Plastic bearing hood
- Chemically resistant washers
- Dual nozzle ports
- Two-year warranty

BENEFITS

- Internal straightening vane increases distance of throw
- Plastic bearing hood protects spring and bearing sleeve from damage
- Corrosion and grit resistant
- Built to last

PERFORMANCE DATA

Straight Bore Nozzle (SBN-5V) with Plug (Stream Height: 4.3m)

BARS @ Nozzle	NOZZLE SIZE														
	8.7 mm (11/32")			9.5 mm (3/8")			10.3 mm (13/32")			11.1 mm (7/16")			11.9 mm (15/32")		
	Rad. (m)	Flow (lps)	Flow (m ³ /h)	Rad. (m)	Flow (lps)	Flow (m ³ /h)	Rad. (m)	Flow (lps)	Flow (m ³ /h)	Rad. (m)	Flow (lps)	Flow (m ³ /h)	Rad. (m)	Flow (lps)	Flow (m ³ /h)
1.7	18.6	1.08	3.88	18.9	1.28	4.61	19.5	1.48	5.31	20.1	1.68	6.06	20.1	1.91	6.88
2.0	19.3	1.16	4.19	19.6	1.38	4.97	20.5	1.59	5.73	20.8	1.82	6.53	21.6	2.06	7.41
2.5	20.6	1.30	4.69	21.0	1.55	5.57	22.2	1.78	6.42	22.8	2.03	7.32	23.7	2.31	8.30
3.0	21.5	1.43	5.16	22.1	1.70	6.11	23.3	1.96	7.05	23.9	2.23	8.03	24.8	2.53	9.11
3.5	22.3	1.55	5.58	22.9	1.84	6.61	24.2	2.12	7.62	24.8	2.41	8.69	25.7	2.74	9.86
4.0	23.2	1.62	5.83	23.8	1.93	6.95	25.1	2.24	8.06	25.8	2.58	9.27	26.6	2.94	10.57
4.5	24.1	1.70	6.12	24.7	2.02	7.28	25.6	2.36	8.51	26.5	2.74	9.85	27.4	3.15	11.35
5.0	24.8	1.81	6.51	25.4	2.14	7.70	26.4	2.50	8.99	27.3	2.90	10.43	28.0	3.30	11.89
5.5	25.3	1.91	6.89	26.2	2.25	8.09	27.1	2.63	9.47	28.0	3.05	10.97	28.6	3.47	12.49
6.0	26.0	2.02	7.26	26.8	2.37	8.52	27.7	2.76	9.94	28.6	3.19	11.49	29.4	3.63	13.07
6.5	26.5	2.13	7.66	27.4	2.48	8.93	28.3	2.89	10.40	29.2	3.33	11.98	29.8	3.77	13.57
6.9	26.8	2.15	7.72	27.7	2.57	9.24	28.7	2.99	10.77	29.6	3.44	12.38	30.2	3.88	13.97
BARS @ Nozzle	NOZZLE SIZE														
	12.7 mm (1/2")			13.5 mm (17/32")			14.3 mm (9/16")			15.9 mm (5/8")			17.5 mm (11/16")		
	Rad. (m)	Flow (lps)	Flow (m ³ /h)	Rad. (m)	Flow (lps)	Flow (m ³ /h)	Rad. (m)	Flow (lps)	Flow (m ³ /h)	Rad. (m)	Flow (lps)	Flow (m ³ /h)	Rad. (m)	Flow (lps)	Flow (m ³ /h)
1.7	20.1	2.13	7.68	20.1	2.34	8.43	20.1	2.67	9.61	20.1	3.25	11.70	20.1	3.91	14.06
2.0	21.8	2.30	8.27	21.8	2.53	9.10	21.8	2.87	10.35	21.8	3.50	12.60	21.8	4.22	15.18
2.5	24.4	2.57	9.26	24.4	2.83	10.19	24.6	3.22	11.60	24.6	3.92	14.12	24.6	4.74	17.06
3.0	25.7	2.83	10.17	26.4	3.11	11.18	27.1	3.54	12.73	27.5	4.31	15.50	27.5	5.22	18.78
3.5	26.6	3.05	11.00	27.5	3.36	12.10	28.7	3.83	13.77	29.1	4.66	16.78	29.7	5.65	20.34
4.0	27.5	3.27	11.79	28.4	3.63	13.06	29.4	4.07	14.66	30.5	4.98	17.93	31.2	6.06	21.82
4.5	28.4	3.49	12.58	29.3	3.87	13.92	30.2	4.39	15.79	31.1	5.33	19.20	32.3	6.45	23.21
5.0	29.0	3.69	13.29	30.0	4.08	14.68	30.9	4.64	16.70	31.8	5.64	20.30	33.1	6.81	24.51
5.5	29.5	3.88	13.96	30.7	4.29	15.44	31.7	4.88	17.57	32.6	5.93	21.33	33.5	7.16	25.77
6.0	30.3	4.05	14.58	31.3	4.49	16.15	32.1	5.10	18.37	33.2	6.20	22.30	34.3	7.49	26.96
6.5	30.7	4.22	15.17	32.0	4.67	16.83	32.8	5.30	19.07	33.8	6.45	23.21	35.0	7.81	28.11
6.9	31.1	4.35	15.65	32.3	4.82	17.35	33.2	5.50	19.81	34.1	6.64	23.89	35.4	8.06	29.00

**Straight Bore Nozzle (SBN-5)
and Spreader (LAN-1-20)** (Stream Height: 4.3m)

BARS @ Nozzle	NOZZLE SIZE														
	8.7 mm x 5.56 mm (11/32" x 7/32") 20°			9.5 mm x 5.56 mm (3/8" x 7/32") 20°			10.3 mm x 5.56 mm (13/32" x 7/32") 20°			11.1 mm x 5.56 mm (7/16" x 7/32") 20°			11.9 mm x 5.56 mm (15/32" x 7/32") 20°		
	Rad.	Flow	Flow	Rad.	Flow	Flow	Rad.	Flow	Flow	Rad.	Flow	Flow	Rad.	Flow	Flow
	(m)	(lps)	(m ³ /h)	(m)	(lps)	(m ³ /h)	(m)	(lps)	(m ³ /h)	(m)	(lps)	(m ³ /h)	(m)	(lps)	(m ³ /h)
1.7	18.6	1.47	5.29	18.9	1.67	6.02	19.5	1.87	6.72	20.1	2.08	7.47	20.1	2.30	8.27
2.0	19.3	1.59	5.71	19.6	1.80	6.49	20.5	2.01	7.23	20.8	2.24	8.05	21.6	2.48	8.92
2.5	20.6	1.78	6.40	21.0	2.02	7.25	22.2	2.25	8.11	22.8	2.50	9.01	23.7	2.78	10.00
3.0	21.5	1.95	7.02	22.1	2.21	7.96	23.3	2.47	8.90	23.9	2.75	9.90	24.8	3.05	10.97
3.5	22.3	2.11	7.60	22.9	2.40	8.63	24.2	2.68	9.63	24.8	2.97	10.71	25.7	3.30	11.88
4.0	23.2	2.26	8.14	23.8	2.57	9.25	25.1	2.88	10.37	25.8	3.19	11.48	26.6	3.54	12.76
4.5	24.1	2.40	8.65	24.7	2.73	9.83	25.6	3.07	11.06	26.5	3.40	12.24	27.4	3.78	13.60
5.0	24.8	2.56	9.21	25.4	2.89	10.40	25.5	3.24	11.67	27.3	3.59	12.92	28.0	3.99	14.35
5.5	25.3	2.68	9.65	26.2	3.04	10.95	27.0	3.42	12.31	28.0	3.78	13.60	28.6	4.20	15.12
6.0	26.0	2.81	10.12	26.8	3.18	11.45	27.7	3.58	12.89	28.6	3.96	14.25	29.4	4.39	15.79
6.5	26.5	2.93	10.55	27.4	3.33	11.98	28.3	3.74	13.48	29.2	4.13	14.88	29.8	4.57	16.46
6.9	26.8	3.02	10.88	27.7	3.44	12.38	28.7	3.86	13.90	29.6	4.26	15.33	30.2	4.72	16.99

PART NUMBERS AND ORDERING INFORMATION

Ordering Example	MAKE YOUR SPRINKLER CHOICE FROM CHART 1	CHOOSE NOZZLE SIZE(S) FROM CHART 2	ADD THEM TOGETHER TO CREATE THE PART NUMBER
To order an 80E sprinkler with an 8.7 mm Brass Straight Bore Nozzle and a 5.56 mm Brass 20° Low Angle Spreader Nozzle the part number would be:	A23803-	22-14	A23803-22-14

Chart 1	PART NUMBER: FIRST HALF
SPRINKLER ONLY	
Sprinkler without Nozzle (NPT)	A23802
SPRINKLER WITH SINGLE NOZZLE INSTALLED	
Sprinkler with SBN-5 and Brass Plug (NPT)	A23813-
Sprinkler with LPN-5 and Brass Plug (NPT)	A23814-
SPRINKLER WITH COMBINATION NOZZLES INSTALLED	
Sprinkler with SBN-5 and LAN-1-20 (NPT)	A23803-
SPRINKLER ONLY	
Sprinkler without Nozzle (BSP)	A23840
SPRINKLER WITH SINGLE NOZZLE INSTALLED	
Sprinkler with SBN-5 and Brass Plug (BSP)	A23851-
SPRINKLER WITH COMBINATION NOZZLES INSTALLED	
Sprinkler with SBN-5 and LAN-1-20 (BSP)	A23841-

Chart 2	PART NUMBER: SECOND HALF										
NOZZLE	5.56 mm	8.7 mm	9.5 mm	10.3 mm	11.1 mm	11.9 mm	12.7 mm	13.5 mm	14.3 mm	15.9 mm	17.5 mm
Brass Straight Bore Nozzle (103043-) SBN-5	-	22	24	26	28	30	32	34	36	40	44
Brass Low Pressure Nozzle (108149-) LPN-5	-	22	24	26	28	30	32	-	-	40	-
Brass 20° Low Angle Spreader Nozzle (100226-) LAN-1-20	14	-	-	-	-	-	-	-	-	-	-