



L36H L36AH

3/4" (19 mm) Full Circle, Plastic, Low Angle Impact Sprinkler

Bearing: 3/4" Male NPT, Brass
Trajectory Angle: 10°
Operating Range: 1.4-4.1 bars
Flow Rate: 0.36-4.04 m³/h
Radius: 12.2-18.76 meters

FEATURES

- Durable Delrin™ plastic body and arm
- AH unit has standard spoon for smaller nozzles
- H unit has slotted spoon for larger nozzles
- Exceptionally wide range of quick-fit nozzles
- Stainless steel springs and fulcrum pin
- Brass bearing sleeve
- Chemically resistant washers
- Dual nozzle ports
- Two-year warranty

BENEFITS

- Superior chemical and grit resistance
- Low angle fights strong wind conditions
- Great choice for pivot or under tree applications
- Easy maintenance
- Added design flexibility
- Built to last

PERFORMANCE DATA (Note: chart data shown on 4 meter riser)

L36AH

L36AH Quick-Fit Straight Bore Nozzle (QF-SBN-3)

BARS @ Nozzle	NOZZLE SIZE								
	2.78 mm (7/64")			3.18 mm (1/8")			3.57 mm (9/64")		
	Rad. (m)	Flow (lps)	Flow (m ³ /h)	Rad. (m)	Flow (lps)	Flow (m ³ /h)	Rad. (m)	Flow (lps)	Flow (m ³ /h)
2.4	13.9	0.13	0.48	14.0	0.17	0.61	14.2	0.21	0.77
2.5	13.9	0.13	0.48	14.1	0.17	0.62	14.2	0.22	0.78
3.0	14.3	0.14	0.52	14.5	0.19	0.67	14.8	0.24	0.85
3.5	14.5	0.15	0.55	15.0	0.20	0.73	15.4	0.25	0.92
4.0	14.7	0.17	0.60	15.2	0.22	0.79	15.8	0.27	0.98
4.1	14.8	0.17	0.61	15.2	0.22	0.79	15.8	0.28	1.00

L36AH Quick-Fit Low Pressure Nozzle (QF-LPN-3)

BARS @ Nozzle	NOZZLE SIZE								
	2.78 mm (7/64")			3.18 mm (1/8")			3.57 mm (9/64")		
	Rad. (m)	Flow (lps)	Flow (m ³ /h)	Rad. (m)	Flow (lps)	Flow (m ³ /h)	Rad. (m)	Flow (lps)	Flow (m ³ /h)
1.4	12.2	0.10	0.36	12.3	0.13	0.48	12.5	0.16	0.59
1.5	12.3	0.11	0.38	12.5	0.14	0.49	12.6	0.17	0.61
2.0	12.7	0.12	0.45	13.0	0.16	0.56	13.2	0.20	0.71
2.5	13.2	0.13	0.48	13.6	0.17	0.62	13.9	0.22	0.78
3.0	13.8	0.15	0.53	13.9	0.19	0.67	14.1	0.24	0.88
3.5	13.9	0.15	0.55	14.0	0.20	0.73	14.2	0.25	0.91