

Distribution Components

Subterranean Emitter Box

Features

- Provides convenient access to subsurface emitter while protecting against vandalism.
- Slotted body facilitates installation of distribution tubing.
- Rugged, UV-resistant thermoplastic construction.

Dimensions

- Height: 10¹/₄" (26 cm)
- Top Diameter: 5" (12,7 cm)
- Base Diameter: 7³/₄" (19,7 cm)

Model

- SEB-6X

12" Polyflex Riser

Features

- Accepts all Xeri-Bubbler™ and Xeri-Spray™ emission devices.
- Constructed of thick-walled, high-density polyethylene.
- Can be used in conjunction with a riser stake (RS-025T) for Xeri-Bug™, Xeri-Bubbler™ and Xeri-Spray™ applications.

Operating Range

- Pressure: 15 to 50 psi (1,0 to 3,5 bar)

Model

- PFR-12

Flex Riser Stake-Threaded

Features

- Constructed of UV-resistant plastic material.
- Barbed side inlet accepts 1/4" vinyl distribution tubing (DT-025).
- 10-32 threaded outlet permits easy threading of 12" (30,5 cm) polyflex riser (PFR-12).

Operating Range

- Pressure: 0 to 50 psi (0 to 3,5 bar)

Model

- RS-025T



SEB-6X



PFR-12



RS-025T