

Distribution Components

**In-Stem
200-mesh Filters**

Features

- Provides 200-mesh filtration for protection from clogs
- Constructed of polyester welded to polypropylene frame
- Use in 1/2" risers and 1/2" threaded multi outlet devices
- Use with Rain Bird 1800 Series spray heads

Models

- 1800 SC 200x
- SRO 050 200x

**Polyflex Riser/
Adapter and Stake
Assemblies**

Features

- Pre-assembly of polyflex riser adapter and stake saves time and money when installing a Xerigation system.
- Use PFR/FRA to install Xerigation emission devices into PVC laterals.
- Use PFR/RS to install Xeri-Sprays™ and Xeri-Bubblers™ in planter beds.

Models

- PFR/FRA
- PFR/RS

**10-32 Thread
Adapter**

Features

- 1/2" (15/21) FPT inlet screws onto any 1/2" (15/21) NPT riser.
- Accepts any Xeri-Bubbler™ or Xeri-Spray™ emission device with 10-32 threads.
- UV-resistant plastic construction.

Operating Range

- Pressure: 0 to 50 psi (0 to 3,5 bar)

Model

- 10-32A

**1800 Xeri-Bubbler
Adapter**

Features

- 10-32 inlet thread accepts Xeri-Bubbler™ or Xeri-Spray™ when adapting to a Rain Bird 1800 Series pop-up spray head or shrub adapter.

Operating Range

- Pressure: 15 to 50 psi (1,0 to 3,5 bar)

Model

- XBA-1800



1800 SC 200x SRO 050 200x



PFR/FRA

PFR/RS



10-32A



XBA-1800

