



LEED® and Rain Bird Water-Efficient Products*

Pressure Regulating Devices

Maintain optimal water pressure. Every 5 psi reduction in pressure reduces water usage by 6-8%. A 70 psi system reduced to a recommended 30 psi can provide more than 50% in water savings.¹

Product

[1800-PRS](#)
[1800-SAM-PRS](#)
[1800-SAM-P45](#)
[RD1800-PRS](#)
[1800 PCS Screens](#)
[5000/5000 Plus with PRS](#)
[TSJ-PRS Swing Joints](#)
[PRS-Dial](#)
[Drip Control Zone Kit](#)

¹ Derived from Bernoulli's equation (5.19). Refer to Roberson/Crowe, *Engineering Fluid Mechanics (Fourth Edition)*, Houghton Mifflin Co., Boston MA 1990

Check Valve Devices

Prevent water from draining out of the system at the lowest sprinkler, which eliminates erosion and run-off.

Product

[1800-SAM/1800-SAM-PRS/1800-SAM-P45](#)
[UNI-Spray™ with SAM](#)
[RD1800-SAM](#)
[3500-SAM](#)
[5000-SAM](#)
[8005 \(SAM pre-installed\)](#)
[6504 \(SAM pre-installed\)](#)
[XFCV Dripline](#)
[XFS-CV Dripline](#)
[RWS Root Watering Series](#)

High Efficiency Nozzles

Provide more uniform distribution of water and eliminate over-spray which can result in 30%+ water savings.²

Product

[R-VAN Rotary Nozzles](#)
[U-Series Nozzles](#)
[HE-VAN Nozzles](#)
[Matched Precipitation Rate \(MPR\) Nozzles](#)
[SQ Square Nozzles \(formerly XPCN\)](#)
[Rain Curtain Nozzles](#)
[5000/5000 Plus MPR Nozzle](#)

² U-Series nozzle water savings based on manufacturer's testing. Rotary-type nozzles use 20-30% less water than traditional spray heads because they operate with lower precipitation rates, greater uniformity of distribution, and a greater radius of coverage, according to the Metropolitan Water District of Southern California. Savings of 22-41% were also shown with rotary-type nozzles in the [CUWA Water Savings Study](#).

Direct-to-Plant-Root Watering Devices

Apply water slowly and directly to the roots of plants, using 30-50% less water than sprinkler irrigation and eliminating overspray and run-off.⁶

Product

[Drip Emission Devices](#)
[XF Series Dripline](#)
[RWS Root Watering Series](#)
[1/4" Landscape Dripline](#)

⁶ Bilderback, T.E., and M.A. Powell. *Efficient Irrigation*. North Carolina Extension Service, Publication Number AG-508-6, March 1996. 21 January 2005.

* All claims of water savings dependent on proper design, installation, and maintenance of irrigation products. Actual water savings may vary from user to user depending on weather, irrigation system and site conditions, and previous irrigation practices.





LEED® and Rain Bird Water-Efficient Products♦

Centralized Control Systems

Enable users of large sites to control multiple controllers, sensors, and other irrigation devices from one central location. Can result in water savings of 25-45% a year, depending on current water management practices.³

Product

[IQ Platform](#)

[Site Control](#)

[Maxicom Central Control](#)

³ Water savings are average values for multiple installations. Case studies verifying these water savings can be found on the LEED website as well as [Rain Bird's Site Report web page](#).

Smart Controller Technologies

Adjust irrigation based on site specific variables including weather and soil moisture level. Smart controllers can reduce water use by up to 40% or more.⁴

Product

[ESP-SMTe Smart Modular Control System](#)

[ESP-LXMEF Controller](#)

[ESP-LX Series with IQ™ Flow Sensing](#)

⁴ Based on water agency (Irvine Ranch Water District, City of Santa Barbara, Cities of Boulder, Longmont, Greenley) and manufacturer case studies of ET-type controllers.

Automatic Controllers with Water Efficient Features

Enables the end user to easily adjust watering cycles to adapt to diverse landscapes and weather/seasonal changes.

Product

[ESP-SMTe Smart Modular Control System](#)

[ESP-TM2 Controller with LNK Wifi Module](#)

[ESP-Me Controller with LNK Wifi Module](#)

[ESP-LXME/F Series](#)

[ESP-LXD Series](#)

Automatic Shut-Off Devices

Automatically shut-off the controller when it is raining or sufficient moisture is detected, resulting in water savings of 15-20%.⁵

Product

[RSD Rain Sensor](#)

[SMRT-Y Soil Moisture Sensor Kit](#)

[WR2 Wireless Rain and Rain/Freeze Sensors](#)

⁵ Water savings confirmed in the Water Efficient Irrigation Study Final Report (May 12, 2003), conducted by the Saving Water Partnership (a coalition of water purveyors in the Puget Sound Region of Washington).

Commercial Pump Stations

Part of a complete reclaimed water irrigation system. VFD pump stations enjoy greater efficiency than constant speed pump stations.

Product

[CLP Series Pump Station](#)

[Low Profile Pump Station \(LP\)](#)

[D-, DP-, DPX- Series Pump Stations](#)

[Engineered Pumping Solutions](#)

♦ All claims of water savings dependent on proper design, installation, and maintenance of irrigation products. Actual water savings may vary from user to user depending on weather, irrigation system and site conditions, and previous irrigation practices.

Rain Bird Corporation

6991 E. Southpoint Road • Tucson, AZ 85756

Phone: (520) 741-6100 • Fax: (520) 741-6522

www.rainbird.com

