# 1300A-F

Adjustable Full-Circle Bubbler

### Features

- Stainless Steel adjustment screw regulates flow and radius for spacing between from 1 to 3 feet (0.3 m to 0.9 m) apart
- Non-corrosive plastic and stainless steel construction for long life
- Shipped with SR-050 1/2" (15/21) inlet filter screen for easy installation and resistance to debris
- Operates over a wide range of pressures
- Five year trade warranty

## **Operating Range**

- Flow: 1.0 to 2.3 gpm (3.6 to 8.4 l/m)
- Spacing: 1 to 3 feet (0.3 to 0.9 m)<sup>1</sup>
- Pressure: 10 to 60 psi (0.7 to 4.1 bar)<sup>2</sup>

## Model

- 1300A-F
- <sup>1</sup> These ranges are based on proper pressure at nozzle
- <sup>2</sup> Rain Bird recommends using 1800 PRS Spray Bodies to maintain optimum nozzle performance in higher pressure situations

1300A-F			
Nozzle	Pressure psi	Flow gpm	
F	10	1.0	
	20	1.4	
	30	1.7	
	40	1.9	
	50	2.1	
	60	2.3	

1300A-	1300A-F		METRIC	
Nozzle	Pressure bar	Flow m³∕h	Flow I/m	
F	0.7	0.23	3.6	
	1.0	0.26	4.2	
	1.5	0.30	4.8	
	2.0	0.34	5.4	
	2.5	0.39	6.0	
	3.0	0.43	7.2	
	3.5	0.48	7.8	
	4.0	0.52	8.4	
	4.1	0.53	8.4	



1300A-F

# 1400 Series

Pressure Compensating Full-Circle Bubblers

### Features

- Low flow rates allow water to be absorbed as needed.
  Reduces runoff
- Flow will not fluctuate at pressures between 20 and 90 psi (1.4 to 6.2 bar)
- · Flow is not adjustable for increased vandal resistance
- Shipped with special SR-050  $^{1\!/}_{2''}$  (15/21) bubbler filter screen for easy installation and resistance to debris
- Trickle pattern on models 1401 and 1402; umbrella pattern on models 1404 and 1408
- Five-year trade warranty

## **Operating Range**

- Flow: 0.25 to 2.00 gpm (1.2 to 7.2 l/m)
- Spacing: 1 to 3 feet (0.3 to 0.9 m)\*
- Pressure: 20 to 90 psi (1.4 to 6.2 bar)

The Intelligent Use of Water.™

## Models

- 1401: 0.25 gpm (0.06 m<sup>3</sup>/h; 0.9 l/m); full-circle, trickle pattern
- 1402: 0.50 gpm (0.11 m<sup>3</sup>/h; 1.8 l/m); full-circle, trickle pattern
- 1404: 1.00 gpm (0.23 m<sup>3</sup>/h; 3.6 l/m); full-circle, umbrella pattern
- 1408: 2.00 gpm (0.46 m<sup>3</sup>/h; 7.2 l/m); full-circle, umbrella pattern
- \* These ranges are based on proper pressure at nozzle. Rain Bird recommends using 1800 PRS Spray Bodies to maintain optimum nozzle performance in higher pressure situations.



1400 Series

33