


- ① FINISH GRADE/TOP OF MULCH
- ② ROOT WATERING SYSTEM:
RAIN BIRD RWS-S
- ③ 1/2" (1,3 CM) SPIRAL BARB FITTING (INCLUDED)
- ④ 1/2" (1,3 CM) SWING ASSEMBLY:
RAIN BIRD SA-125050
OR
1/2" (1,3 CM) SWING PIPE:
RAIN BIRD SP SERIES WITH 1/2" (1,3 CM)
MALE NPT x 0.490" BARB ELBOW:
RAIN BIRD SBE-050
- ⑤ PVC SCH 40 TEE OR EL
- ⑥ PVC OR POLYETHYLENE LATERAL PIPE
- ⑦ SHRUB ROOT BALL

NOTES:

- 1. PLACE TOP OF RWS-S EVEN WITH FINISH GRADE OR TOP OF MULCH.
- 2. SPACE RWS-S EVENLY BETWEEN SHRUBS, AS SHOWN ABOVE.
- 3. RWS-S IS AVAILABLE IN THE FOLLOWING MODELS:
RWS-S-B-C-1401: 0.25 GPM (0,95 L/M), CHECK VALVE
RWS-S-B-1401: 0.25 GPM (0,95 L/M)
- 4. ONCE RWS-S HAS BEEN INSTALLED FILL THE BASKET WITH PEA GRAVEL BEFORE REPLACING SNAP-ON LID.



ROOT WATERING SYSTEM RWS-S

N.T.S.

INSTALLATION FOR SHRUBS

07-19-2013