


- ① FINISH GRADE/TOP OF MULCH
- ② ROOT WATERING SYSTEM: RAIN BIRD RWS-M
- ③ 1/2" (1,3 CM) SPIRAL BARB FITTING (INCLUDED)
- ④ 1/2" (1,3 CM) SWING ASSEMBLY: RAIN BIRD SA-125050  
OR  
1/2" (1,3 CM) SWING PIPE: RAIN BIRD SP SERIES WITH  
1/2" (1,3 CM) MALE NPT x 0.490" BARB ELBOW:  
RAIN BIRD SBE-050
- ⑤ PVC SCH 40 TEE OR EL
- ⑥ PVC OR POLYETHYLENE LATERAL PIPE
- ⑦ OPTIONAL SOCK (RWS-SOCK) FOR SANDY SOILS
- ⑧ 4" (10,2 CM) WIDE X 18" (45,7 CM) LONG RIGID  
BASKET WEAVE CANISTER (INCLUDED)
- ⑨ PLANT ROOT BALL

#### NOTES:

1. POSITION 2-3 UNITS (OR MORE) EVENLY SPACED AROUND PLANT. FOR NEW TREES PLACE NEAR ROOT BALL. FOR EXISTING TREES PLACE HALF THE DISTANCE BETWEEN CANOPY EDGE AND TREE TRUNK.
2. INSTALL PRODUCT WITH TOP EVEN WITH FINISH GRADE OR THE TOP OF MULCH
3. RWS-M SERIES AVAILABLE IN THE FOLLOWING MODELS:  
RWS-M-B-C-1401: 0.25 GPM (0,95 L/M), CHECK VALVE  
RWS-M-B-1401: 0.25 GPM (0,95 L/M)  
RWS-M-B-C-1402: 0.5 GPM (1,9 L/M), CHECK VALVE  
RWS-M-B-1402: 0.5 GPM (1,9 L/M),
4. WHEN INSTALLING IN EXTREMELY HARD OR CLAY SOILS, ADD 3/4" (1,9 CM) GRAVEL UNDER AND AROUND THE UNIT TO ALLOW FASTER WATER INFILTRATION AND ROOT PENETRATION.
5. ONCE RWS-M HAS BEEN INSTALLED FILL THE BASKET WITH PEA GRAVEL BEFORE LOCKING LID.
6. OPTIONAL RWS-SOCK FOR USE IN SANDY SOILS.



## ROOT WATERING SYSTEM **RWS-M**

### INSTALLATION FOR TREES

N.T.S.

07-19-2013