

(1) IRRIGATION CONTROLLER:

RAIN BIRD IQ ESP—LXME SATELLITE CONTROLLER WITH

IO NOC CORS CARTRIDGE IN PLASTIC CARDINET WITH

IQ NCC GPRS CARTRIDGE IN PLASTIC CABINET WITH WALL MOUNT. INSTALL CONTROLLER AND CABINET ON WALL PER MANUFACTURER'S RECOMMENDATIONS.

- (2) JUNCTION BOX
- $\left(3\right)$ 1-inch conduit and fittings to power supply
- (4) POWER SUPPLY WIRE
- (5) 2-INCH CONDUIT AND FITTINGS FOR STATION WIRES
- (6) WIRES TO REMOTE CONTROL VALVES

NOTES:

- 1. IQ ESP-LXME CONTROLLER IS AVAILABLE IN 8- OR 12-STATION BASE MODELS.

 ADDITIONAL MODULES IN 4-, 8- AND 12-STATION VERSIONS MAY BE ADDED TO BRING THE CONTROLLER UP TO 48 STATIONS MAXIMUM.
- 2. FOR EASE OF INSTALLATION INTO A CONTROLLER WITH MORE THAN 24 STATIONS, INSTALL A JUNCTION BOX AT THE BASE OF CONTROLLER AND TRANSITION LARGER VALVE AND COMMON WIRES FROM FIELD TO 18 AWG MULTI CONDUCTOR WIRE TO BE USED IN CONTROLLER.
- 3. USE STEEL CONDUIT FOR ABOVE GRADE AND SCH 40 PVC CONDUIT FOR BELOW GRADE CONDITIONS.
- 4. PROVIDE PROPER GROUNDING COMPONENTS TO ACHIEVE GROUND RESISTANCE OF 10 OHMS OR LESS.
- 5. IQ NCC GPRS CARTRIDGE COMES WITH AN INTERNAL ANTENNA FOR USE WITH PLASTIC CABINET. INSTALL CONTROLLER IN A LOCATION TO MAXIMIZE ANTENNA RECEPTION. CONDUCT A SURVEY OF THE SITE TO ASSURE A VIABLE AND CONSISTENT CELLULAR CONNECTION BEFORE INSTALLING CONTROLLER. OWNER IS RESPONSIBLE FOR PROVIDING CELLULAR SERVICE CAPABLE OF INTERFACING WITH NCC GPRS CARTRIDGE.



1-12-

 $D \rightarrow N.T.$

LXM040.DWG

IN PLASTIC CABINET