



- ① PRESSURE-COMPENSATING MODULE BARB INLET X BARB OUTLET EMITTER WITH PC DIFFUSER CAP:  
RAIN BIRD PC EMITTER WITH PC DIFFUSER  
(1 OF 2 SHOWN, 6 POSSIBLE)
- ② UNIVERSAL ¼" TUBING STAKE:  
RAIN BIRD TS-025  
(1 OF 2 SHOWN, 6 POSSIBLE)
- ③ ¼" DISTRIBUTION TUBING:  
RAIN BIRD XQ TUBING (LENGTH AS REQUIRED)  
(1 OF 2 SHOWN, 6 POSSIBLE)
- ④ SUBTERRANEAN EMITTER BOX:  
RAIN BIRD SEB 7XB
- ⑤ SIX OUTLET MANIFOLD:  
RAIN BIRD EMT-6XERI
- ⑥ TOP OF MULCH
- ⑦ FINISH GRADE
- ⑧ PVC SCH 80 NIPPLE  
(LENGTH AS REQUIRED)
- ⑨ PVC SCH 40 TEE OR ELL
- ⑩ PVC LATERAL PIPE
- ⑪ 3" MINIMUM DEPTH OF  
¾" WASHED GRAVEL

NOTES:

1. SHOULD THE EMITTER BECOME DISLODGED UNREGULATED FLOW WILL OCCUR.
2. RAIN BIRD PC BARB X BARB EMITTERS ARE AVAILABLE IN THE FOLLOWING MODELS:
 

PC-05	5 GPH	PC-07	7 GPH	PC-10	10 GPH
PC-12	12 GPH	PC-18	18 GPH	PC-24	24 GPH
3. PC DIFFUSER CAPS ARE AVAILABLE IN BOTH BLACK AND PURPLE.

**PRESSURE COMPENSATING MODULE WITH  
PC DIFFUSER CAP FROM SIX OUTLET**

N.T.S.

**MANIFOLD WITH 1/4" TUBING AND  
STAKE - OPTION 5A**

1-13-10

