


- ① MULCH
- ② FLUSH CAP FOR EASY FIT
COMPRESSION FITTINGS:
POTABLE: RAIN BIRD MDCFCAP
- ③ EASY FIT COUPLING:
RAIN BIRD MDCFCOUP
- ④ SUBTERRANEAN EMITTER BOX:
RAIN BIRD SEB 7XB
- ⑤ ½" POLYETHYLENE TUBING:
RAIN BIRD XF BLANK TUBING
- ⑥ FINISH GRADE
- ⑦ PVC EXHAUST HEADER
- ⑧ PVC SCH 40 TEE OR EL
- ⑨ BARB X MALE FITTING:
RAIN BIRD XFF-MA FITTING (TYPICAL)
- ⑩ ON-SURFACE DRIPLINE:
RAIN BIRD XF SERIES DRIPLINE
POTABLE: XFCV DRIPLINE
- ⑪ 3-INCH MINIMUM DEPTH OF
¾" WASHED GRAVEL
- ⑫ BRICK (1 OF 2)

NOTE:

- 1. ALLOW A MINIMUM OF 6-INCHES OF DRIPLINE TUBING IN VALVE BOX IN ORDER TO DIRECT FLUSHED WATER OUTSIDE VALVE BOX.



XFCV ON-SURFACE DRIPLINE FLUSH POINT

02-18-2013

N.T.S.

WITH EASY FIT COMPRESSION FITTINGS