



- ① TWIST LOCK FITTING : TLF-TEE 0600
- ② ON-SURFACE DRIPLINE:
RAIN BIRD XFS-CV SERIES DRIPLINE (TYPICAL)
NON-POTABLE: XFS-CVP DRIPLINE
- ③ INLINE DRIP EMITTER OUTLET
- ④ TIE DOWN STAKE: RAIN BIRD TDS-050 WITH BEND (TYPICAL)
- ⑤ MULCH
- ⑥ FINISH GRADE
- ⑦ 1/2" POLYETHYLENE TUBING:
RAIN BIRD XFD SERIES BLANK TUBING
- ⑧ TWIST LOCK FITTING : TLF-MPT6-0600
- ⑨ 1"X1"X1/2" SST PVC TEE
- ⑩ PVC LATERAL PIPE
MINIMUM 1" IN DIAMETER

NOTES:

- 1. PLACE TIE DOWN STAKES EVERY THREE FEET IN SAND, FOUR FEET IN LOAM, AND FIVE FEET IN CLAY.
- 2. AT FITTINGS WHERE THERE IS A CHANGE OF DIRECTION SUCH AS TEES OR ELBOWS, USE TIE-DOWN STAKES ON EACH LEG OF THE CHANGE OF DIRECTION.

D **XFS-CV ON-SURFACE DRIPLINE INSERT ADAPTER** 05-17-2017
 N.T.S. **FOR 1" OR LARGER PVC**