

NOTES:

- 1. PLACE TIE DOWN STAKES EVERY THREE FEET IN SAND, FOUR FEET IN LOAM, AND FIVE FEET IN CLAY.
- 2. AT FITTINGS WHERE THERE IS A CHANGE OF DIRECTION SUCH AS TEES OR ELBOWS, USE TIE—DOWN STAKES ON EACH LEG OF THE CHANGE OF DIRECTION.
- 3. SAVE YOUR HANDS. USE THE RAIN BIRD FITTINS—TOOL XF INSERTION TOOL FOR FITTING ASSEMBLY.

- 1 BARB ELBOW 17x17mm RAIN BIRD XFF-ELBOW
- 2 ON-SURFACE DRIPLINE:
 RAIN BIRD XFS-CV SERIES DRIPLINE
 (TYPICAL)
 NON-POTABLE: XFS-CVP DRIPLINE
- 3 BARB TEE 17x17x17mm RAIN BIRD XFF-TEE
- (4) INLINE DRIP EMITTER OUTLET, SEE PLANS FOR DRIPLINE OUTLET SPACING.
- 5) BARB COUPLING 17x17mm RAIN BIRD XFF-COUP
- 6 TIE DOWN STAKE: RAIN BIRD TDS-050 WITH BEND (TYPICAL)
- 7) MULCH
- (8) FINISH GRADE
- (9) PVC LATERAL SUPPLY HEADER
- (10) PVC TEE SxSxT
- 11) BARB MALE ADAPTER
 17mm X 1/2" MPT
 RAIN BIRD XFF-MA-050
 17mm X 3/4" MPT
 RAIN BIRD XFF-MA-075
- (12) RAIN BIRD XFS-CV SERIES BLANK TUBING LENGTH AS REQUIRED



XFS-CV ON-SURFACE DRIPLINE RISER ASSEMBLY 05-17-2017

N.T.S.