



- ① OPERATION INDICATOR
RAIN BIRD MODEL: OPERIND
- ② SUB-SURFACE/ON-SURFACE DRIPLINE:
RAIN BIRD XFS-CV SERIES DRIPLINE (TYPICAL)
NON-POTABLE: XFS-CVP DRIPLINE
- ③ PERIMETER OF AREA
- ④ PERIMETER LATERALS 2" TO 4" FROM
EDGE OF LANDSCAPE
- ⑤ QF SUPPLY HEADER
- ⑥ FLUSH POINT (TYPICAL)
SEE RAIN BIRD DETAIL "XFS-CV FLUSH POINT"
- ⑦ QF EXHAUST HEADER
- ⑧ TIE DOWN STAKES
RAIN BIRD TDS-050 WITH BEND
- ⑨ IRRIGATION CONTROL VALVE:
RAIN BIRD XCZ DRIP CONTROL ZONE KIT
INSTALLED IN VALVE BOX

NOTES:

- 1. FOR ALL QF HEADER CONNECTIONS INSTAL TLF
SERIES TWIST LOCK FITTINGS.
- 2. RECOMMENDED MINIMUM FILTRATION: 120 MESH
- 3. PRESSURE AT FLUSH VALVE SHALL BE MIN 14.5 PSI
- 4. MAX 10' OF WATER(ELEVATION CHANGE)
- 5. REFER TO MAXIMUM LENGTH OF A SINGLE LATERAL
CHART
- 6. CHECK VALVE TYPE AND SIZE SHALL BE SPECIFIED
BY ORIENTATION AND FLOW REQUIREMENTS NOT LINE
SIZE

D XFS-CV SUB-SURFACE/ON SURFACE DRIPLINE 05-17-2017 N.T.S.
3 VALVES - INDIVIDUAL GRIDS TOE OF SLOPE LAYOUT W/ QF HEADER