

- 1) SUB-SURFACE/ON-SURFACE DRIPLINE: RAIN BIRD XFS-CV SERIES DRIPLINE NON-POTABLE: XFS-CVP DRIPLINE
- (2)inline drip emitter outlet
- 3) TIE DOWN STAKE: RAIN BIRD TDS-050 WITH BEND (TYPICAL)
- 4) TURF/FINISH GRADE OR SHRUB BED WITH MULCH
- (5) BARB X BARB INSERT RAIN BIRD XFF-ELBOW
- 6 1/2" RAIN BIRD XF SERIES BLANK TUBING
- (7) TWIST LOCK FITTING: TLF-MPT8-0600
- 8 1 1/2" X 1 1/2" X 3/4" SST PVC TEE
- 9 PVC LATERAL
 MINIMUM 1 1/2" IN DIAMETER
 DEPTH PER SPECIFICATION

NOTES:

- 1. PLACE TIE DOWN STAKES EVERY THREE FEET IN SAND, FOUR FEET IN LOAM, AND FIVE FEET IN CLAY.
- 2. AT FITTINGS WHERE THERE IS A CHANGE OF DIRECTION SUCH AS TEES OR ELBOWS, USE TIE-DOWN STAKES ON EACH LEG OF THE CHANGE OF DIRECTION.
- 3. INSERTION PLOW AND TRENCHED INSTALLATIONS DO NOT REQUIRE TIE DOWN STAKES.



XFS-CV SUB-SURFACE DRIPLINE INSERT

05-17-2017

N.T.S.

ADAPTER FOR 1 1/2" OR LARGER PVC