



- ① MULCH
- ② FLUSH CAP FOR TWIST LOCK FITTINGS:
POTABLE: RAIN BIRD TLF-CAP
- ③ TWIST LOCK FITTING TLF-MPT
- ④ SUBTERRANEAN EMITTER BOX:
RAIN BIRD SEB 7XB
- ⑤ 1/2" RAIN BIRD XF BLANK TUBING
- ⑥ FINISH GRADE
- ⑦ PVC EXHAUST HEADER
- ⑧ PVC SCH 40 TEE OR EL
- ⑨ BARB X MALE FITTING:
RAIN BIRD XFF-MA FITTING (TYPICAL)
- ⑩ SUB-SURFACE/ON-SURFACE DRIPLINE:
RAIN BIRD XFS-CV SERIES DRIPLINE (TYPICAL)
NON-POTABLE: XFS-CVP DRIPLINE
- ⑪ 3-INCH MINIMUM DEPTH OF
3/4" WASHED GRAVEL
- ⑫ BRICK (1 OF 2)

NOTE:
1. ALLOW A MINIMUM OF 6-INCHES OF DRIPLINE TUBING IN VALVE BOX IN ORDER TO DIRECT FLUSHED WATER OUTSIDE VALVE BOX.

D XFS-CV SUB-SURFACE/ON-SURFACE DRIPLINE FLUSH POINT 05-17-2017
N.T.S. WITH RAIN BIRD TLF FITTINGS