



- ① XFS-CV SPACING PER RAIN BIRD RECOMMENDATION
- ② PVC OR DRIPLINE EXHAUST HEADER
- ③ SUB-SURFACE/ON-SURFACE DRIPLINE:  
RAIN BIRD XFS-CV SERIES DRIPLINE (TYPICAL)  
NON-POTABLE: XFS-CVP DRIPLINE
- ④ FLUSH POINT (TYPICAL)  
SEE RAIN BIRD DETAIL "XFS-CV FLUSH POINT"
- ⑤ OPERATION INDICATOR  
RAIN BIRD MODEL: OPERIND
- ⑥ TREE TRUNK
- ⑦ PVC OR DRIPLINE SUPPLY HEADER
- ⑧ IRRIGATION CONTROL VALVE:  
RAIN BIRD XCZ DRIP CONTROL ZONE KIT  
INSTALLED IN VALVE BOX
- ⑨ BARB X BARB INSERT CROSS:  
RAIN BIRD XFD-CROSS (TYPICAL)
- ⑩ TIE DOWN STAKE:  
RAIN BIRD TDS-050 WITH BEND

NOTE:

- 1. FOR ALL XFS-CV AND POLY CONNECTIONS INSTALL XFF AND/OR XFD FITTINGS
- 2. LAYOUT TO BE UTILIZED FOR LARGE SYSTEMS & REDUCTION OF FLUSH POINTS.

**D XFS-CV SUB-SURFACE/ON-SURFACE DRIPLINE** 05-17-2017  
N.T.S. **MULTIPLE TREE RING LAYOUT DUAL FED**