



- ① SQUARE CONFIGURATION
- ② FLUSH POINT (TYPICAL)
SEE RAIN BIRD DETAIL "XFS-CV FLUSH POINT"
- ③ RAIN BIRD XF SERIES BLANK TUBING
- ④ TREE TRUNK
- ⑤ SUB-SURFACE/ON-SURFACE DRIPLINE:
RAIN BIRD XFS-CV SERIES DRIPLINE (TYPICAL)
NON-POTABLE: XFS-CVP DRIPLINE
- ⑥ XFS-CV SPACING PER RAIN BIRD
RECOMMENDATION
- ⑦ OPERATION INDICATOR
RAIN BIRD MODEL: OPERIND
- ⑧ PVC SUPPLY HEADER (SIZE BASED ON TOTAL
FLOW)
- ⑨ IRRIGATION CONTROL VALVE:
RAIN BIRD XCZ DRIP CONTROL ZONE KIT
INSTALLED IN VALVE BOX
- ⑩ BARB X BARB INSERT CROSS:
RAIN BIRD XFD-CROSS (TYPICAL)
- ⑪ TIE DOWN STAKE:
RAIN BIRD TDS-050 WITH BEND

NOTES:

- 1. FOR ALL XFS-CV AND POLY CONNECTIONS INSTALL XFF AND/OR XFD FITTINGS
- 2. SEE XFS-CV TREE RING DOUBLE OR TRIPLE FOR DETAIL OF EACH SET OF RINGS.
- 3. FOR TOTAL SYSTEM FLOW GREATER THAN 5 GPM USE PVC TO CONNECT TREE RINGS, DOUBLE OR TRIPLE, AND SIZE PVC APPROPRIATELY.

D XFS-CV SUB-SURFACE/ON-SURFACE DRIPLINE 05-17-2017
N.T.S. **MULTIPLE TREE RING LAYOUT SIDE FED**