



- ① FLUSH POINT (TYPICAL)
SEE RAIN BIRD DETAIL "XFS-CV FLUSH POINT"
- ② PVC OR DRIPLINE EXHAUST HEADER
- ③ SUB-SURFACE/ON-SURFACE DRIPLINE:
RAIN BIRD XFS-CV SERIES DRIPLINE (TYPICAL)
NON-POTABLE: XFS-CVP DRIPLINE
- ④ RAIN BIRD XFF-TEE FITTING
- ⑤ TREE TRUNK
- ⑥ TIE DOWN STAKES
RAIN BIRD TDS-050 WITH BEND
- ⑦ XFS-CV SPACING PER RAIN BIRD GUIDELINES
- ⑧ PVC OR DRIPLINE SUPPLY HEADER
- ⑨ RAIN BIRD XFD-CROSS FITTING
- ⑩ RAIN BIRD TLF-TEE OR XFF-TEE FITTING
- ⑪ SCHEDULE 40 PVC DRIP LATERAL

NOTES:

1. FOR ALL XFS-CV AND POLY CONNECTIONS INSTALL XFF AND/OR XFD FITTINGS.
2. INSTALL EACH LOOP PER RAIN BIRD INSTALLATION GUIDELINES
3. INSTALL XFS-CV DRIPLINE ON SURFACE TO MAXIMUM OF 6 INCHES BELOW GRADE, STAPLE IN PLACE PER MANUFACTURERS RECOMMENDATIONS. BACKFILL AND SPREAD SURFACE TREATMENT AS DIRECTED BY OTHERS
4. INSTALL XFS-CV DRIPLINE IN ACCORDANCE WITH RAIN BIRD GUIDELINES

D **XFS-CV SUB-SURFACE/ON-SURFACE DRIPLINE** 05-17-2017
N.T.S. **THREE TREE RING LAYOUT**