



- ① FLUSH POINT (TYPICAL)
SEE RAIN BIRD DETAIL "XFS-CV FLUSH POINT"
- ② SUB-SURFACE/ON-SURFACE DRIPLINE:
RAIN BIRD XFS-CV SERIES DRIPLINE (TYPICAL)
NON-POTABLE: XFS-CVP DRIPLINE
- ③ 1/2" OR 3/4" THREADED PVC TEE W/ XFF-MA
& XFF-ELBOW
- ④ EXHAUST HEADER PVC OR POLY
- ⑤ SEE SPECIFICATIONS FOR ROW SPACING
- ⑥ RAIN BIRD XFF-TEE
- ⑦ PERIMETER LATERALS 2" TO 4" FROM EDGE
- ⑧ IRRIGATION CONTROL VALVE:
RAIN BIRD XCZ DRIP CONTROL ZONE KIT
INSTALLED IN VALVE BOX
- ⑨ AREA PERIMETER
- ⑩ PVC SUPPLY HEADER
- ⑪ OPERATION INDICATOR
RAIN BIRD MODEL: OPERIND

NOTES:

1. FOR ALL XFS-CV AND POLY CONNECTIONS INSTALL XFF AND/OR XFD FITTINGS
2. RECOMMENDED MINIMUM FILTRATION: 120 MESH
3. PRESSURE AT FLUSH VALVE SHALL BE MIN 15 PSI
4. 2 PSI CHECK VALVE (MAX 9' OF WATER(ELEVATION CHANGE))
5. REFER TO MAXIMUM LENGTH OF A SINGLE LATERAL CHART

D XFS-CV SUB-SURFACE/ON SURFACE DRIPLINE 05-17-2017
TRIANGULAR PATTERN W/ PVC HEADER N.T.S.