


- ① SUB-SURFACE DRIPLINE:
RAIN BIRD XF SERIES DRIPLINE
POTABLE: XFS DRIPLINE
NON-POTABLE: XFSP DRIPLINE
- ② INLINE DRIP EMITTER OUTLET
- ③ TIE DOWN STAKE: RAIN BIRD
TDS-050 WITH BEND (TYPICAL)
- ④ TURF/FINISH GRADE OR SHRUB BED
WITH MULCH
- ⑤ RATCHET CLAMP (INCLUDED WITH
ADAPTER)
- ⑥ INSERT ADAPTER FOR PVC PIPE:
RAIN BIRD XFD-INVPC
- ⑦ PVC LATERAL PIPE
MINIMUM 1½" IN DIAMETER
DEPTH PER SPECIFICATION

NOTES:

- 1. PLACE TIE DOWN STAKES EVERY THREE FEET IN SAND, FOUR FEET IN LOAM, AND FIVE FEET IN CLAY.
- 2. AT FITTINGS WHERE THERE IS A CHANGE OF DIRECTION SUCH AS TEES OR ELBOWS, USE TIE-DOWN STAKES ON EACH LEG OF THE CHANGE OF DIRECTION.
- 3. INSERTION PLOW AND TRENCHED INSTALLATIONS DO NOT REQUIRE TIE DOWN STAKES.



XFS SUB-SURFACE DRIPLINE INSERT

N.T.S.

ADAPTER FOR 1 1/2" OR LARGER PVC

12-18-2012