


- ① PVC DRIP MANIFOLD PIPE
- ② PVC SCH 40 TEE OR EL
- ③ RAIN BIRD XF SERIES BLANK TUBING
- ④ BARB CROSS INSERT FITTING:
RAIN BIRD XFD-CROSS
- ⑤ BARB TEE INSERT FITTING:
RAIN BIRD XFF-TEE
- ⑥ PROJECTED CANOPY LINE OF TREE
- ⑦ SUB-SURFACE DRIPLINE:
RAIN BIRD XF SERIES DRIPLINE
POTABLE: XFS DRIPLINE
NON-POTABLE: XFSP DRIPLINE
PLACE AS SHOWN (LENGTH AS
REQUIRED)
- ⑧ ROOT BALL
- ⑨ TIE DOWN STAKE:
RAIN BIRD TDS-050 WITH BEND
(QUANTITY AS REQUIRED,
SEE NOTES 2-3 BELOW)

NOTES:

1. DISTANCE BETWEEN LATERAL RINGS AND EMITTER SPACING TO BE BASED ON SOIL TYPE, AND TREE CANOPY. SEE RAIN BIRD XF-SDI DRIPLINE INSTALLATION GUIDE FOR SUGGESTED SPACINGS.
2. PLACE TIE DOWN STAKES EVERY THREE FEET IN SAND, FOUR FEET IN LOAM, AND FIVE FEET IN CLAY.
3. AT FITTINGS WHERE THERE IS A CHANGE OF DIRECTION SUCH AS TEES OR ELBOWS, USE TIE-DOWN STAKES ON EACH LEG OF THE CHANGE OF DIRECTION.



XFS SUB-SURFACE DRIPLINE AROUND TREE

12-18-2012

N.T.S.