

- ① 30-INCH LINEAR LENGTH OF WIRE, COILED
- ② WATERPROOF CONNECTION: RAIN BIRD SPLICE-1 (1 OF 2)
- ③ ID TAG: RAIN BIRD VID SERIES
- ④ REMOTE CONTROL VALVE: RAIN BIRD 300-BPES-PRS-D WITH BSP THREADS
- ⑤ VALVE BOX WITH COVER: RAIN BIRD VB-STD WITH 6-INCH EXTENSION
- ⑥ FINISH GRADE/TOP OF MULCH
- ⑦ BRICK (1 OF 4)
- ⑧ MAINLINE PIPE
- ⑨ DUCTILE IRON SERVICE TEE
- ⑩ DUCTILE IRON NIPPLE (6-INCH LENGTH)
- ⑪ PVC REDUCING MALE ADAPTER
- ⑫ PVC LATERAL PIPE
- ⑬ 3.0-INCH MINIMUM DEPTH OF 3/4-INCH WASHED GRAVEL



**ELECTRIC REMOTE-CONTROL VALVE**  
 N.T.S. **300BPE OR 300BPES BOTTOM INLET**


1-19-04

**CHOOSING EQUIPMENT CALLOUT METHOD**

CHOOSE EITHER LEADERS OR BUBBLE CALLOUTS BY TURNING ON THE APPROPRIATE LAYER:

TEXT\_LEADERS

TEXT\_BUBBLES



TO TURN OFF THIS INSTRUCTION BOX, TURN OFF LAYER "INSTRUCT-CALLOUT".

**CHOOSING VALVES AND OPTIONS**

VALVES

CHOOSE ONE OF THE FOLLOWING VALVES BY TURNING ON THE APPROPRIATE LAYER:

REMOTE CONTROL VALVE  
 OPTION-SOLENOID

PRESSURE REGULATING REMOTE CONTROL VALVE

OPTION-PRS-D

AND EITHER:  
 TEXT-BPE-PRS-D-LEADERS OR  
 TEXT-BPE-PRS-D-BUBBLES

SCRUBBER VALVE

OPTION-SOLENOID

AND EITHER:  
 TEXT-BPES-LEADERS OR  
 TEXT-BPES-BUBBLES

PRESSURE REGULATING SCRUBBER VALVE

OPTION-PRS-D

AND EITHER:  
 TEXT-BPES-PRS-D-LEADERS OR  
 TEXT-BPES-PRS-D-BUBBLES

OPTIONS

CHOOSE ONE OF THE FOLLOWING OPTIONS BY TURNING ON THE APPROPRIATE LAYER:

BSP THREADS

EITHER:  
 TEXT-BSP-LEADERS OR  
 TEXT-BSP-BUBBLES

NP HANDLE

EITHER:  
 TEXT-NPHAN-LEADERS OR  
 TEXT-NPHAN-BUBBLES

TO TURN OFF THIS INSTRUCTION BOX, TURN OFF LAYER "INSTRUCT-OPTION".