


- ① 30-INCH LINEAR LENGTH OF WIRE, COILED
- ② WATERPROOF CONNECTION: RAIN BIRD SPLICE-1 (1 OF 2)
- ③ ID TAG: RAIN BIRD VID SERIES
- ④ REMOTE CONTROL VALVE: RAIN BIRD 300-BPE-PRS-D WITH BSP THREADS
- ⑤ VALVE BOX WITH COVER: RAIN BIRD VB-STD WITH 6-INCH EXTENSION
- ⑥ FINISH GRADE/TOP OF MULCH
- ⑦ DUCTILE IRON 90° EL
- ⑧ BRICK (1 OF 4)
- ⑨ MAINLINE PIPE
- ⑩ DUCTILE IRON SERVICE TEE
- ⑪ DUCTILE IRON COUPLING
- ⑫ DUCTILE IRON NIPPLE (4-INCH LENGTH)
- ⑬ PVC REDUCING MALE ADAPTER
- ⑭ PVC LATERAL PIPE
- ⑮ 3.0-INCH MINIMUM DEPTH OF 3/4-INCH WASHED GRAVEL

CHOOSING EQUIPMENT CALLOUT METHOD

CHOOSE EITHER LEADERS OR BUBBLE CALLOUTS BY TURNING ON THE APPROPRIATE LAYER:



TO TURN OFF THIS INSTRUCTION BOX, TURN OFF LAYER "INSTRUCT-CALLOUT".

CHOOSING VALVES AND OPTIONS

VALVES
CHOOSE ONE OF THE FOLLOWING VALVES BY TURNING ON THE APPROPRIATE LAYER:

REMOTE CONTROL VALVE
OPTION-SOLENOID

SCRUBBER VALVE
OPTION-SOLENOID
AND EITHER:
TEXT-BPES-LEADERS OR
TEXT-BPES-BUBBLES

PRESSURE REGULATING
REMOTE CONTROL VALVE
OPTION-PRS-D
AND EITHER:
TEXT-BPE-PRS-D-LEADERS OR
TEXT-BPE-PRS-D-BUBBLES

PRESSURE REGULATING
SCRUBBER VALVE
OPTION-PRS-D
AND EITHER:
TEXT-BPES-PRS-D-LEADERS OR
TEXT-BPES-PRS-D-BUBBLES

OPTIONS
CHOOSE ONE OF THE FOLLOWING OPTIONS BY TURNING ON THE APPROPRIATE LAYER:

BSP THREADS
EITHER:
TEXT-BSP-LEADERS OR
TEXT-BSP-BUBBLES

NP HANDLE
EITHER:
TEXT-NPHAN-LEADERS OR
TEXT-NPHAN-BUBBLES

TO TURN OFF THIS INSTRUCTION BOX, TURN OFF LAYER "INSTRUCT-OPTION".



ELECTRIC REMOTE-CONTROL VALVE
N.T.S.
300BPE OR 300BPES

1-19-04