


- ① TWO-WIRE CABLE
- ② WATERPROOF SPLICE CONNECTION: RAIN BIRD WC20 (TWO REQUIRED)
- ③ ID TAG
- ④ REMOTE CONTROL VALVE: RAIN BIRD 300-BPES WITH IVM-SOL
- ⑤ VALVE BOX WITH COVER: RAIN BIRD VB-JUMBO WITH 6-INCH EXTENSION
- ⑥ FINISH GRADE/TOP OF MULCH
- ⑦ DUCTILE IRON 90° EL
- ⑧ BRICK (1 OF 4)
- ⑨ MAINLINE PIPE
- ⑩ DUCTILE IRON SERVICE TEE
- ⑪ DUCTILE IRON COUPLING
- ⑫ DUCTILE IRON NIPPLE (4-INCH LENGTH)
- ⑬ PVC MALE ADAPTER
- ⑭ PVC LATERAL PIPE
- ⑮ 3-INCH MINIMUM DEPTH OF 3/4-INCH WASHED GRAVEL

NOTE:
 1. COIL AN ADDITIONAL 3-FEET OF TWO-WIRE CABLE IN VALVE BOX FOR EASY SERVICING.



ELECTRIC REMOTE-CONTROL VALVE

N.T.S.

300-BPES WITH IVM-SOL